

UNIQUE TREAD DESIGN

Excellent self cleaning
Better fuel economy

RAISED CENTER RIBS

Provides better roadability
Higher productivity

CUT & CHIP RESISTANCE TREAD COMPOUND

Resists Stubble Damage
Extensive tire life



FT2 (F2)
BIAS TIRES BUILT FOR
TRACTORS



- Specially designed for 2WD tractors in soil tillage and transport applications
- Optimum Land/Sea Ratio for improved traction on and off road
- Strong Casing with Cut/Wear Resistant Compound for higher productivity

Traction



Roadability



Tire Life



Soil Protection



TYRE SIZE	
16.0	18.0
5.00-16	7.50-18
6.00-16	20.0
6.50-16	6.50-20
7.50-16	7.50-20
10.00-16	

TECHNICAL DATA

	TYRE SIZE	PR	TT / TL	RIM		Unloaded Inflated Dimension		SLR	RC	At Speed 30 kmph (20 mph)			At Speed 40 kmph (25 MPH)			Inflation Pressure		
						SW	OD			Speed Index	Load Index	MAX. LOAD	Speed Index	Load Index	MAX. LOAD			
				Rec. inch	Alt. inch	± 2 % Inch	± 2 % Inch	Inch	± 2.5 % inch			(lbs)			(lbs)	Kpa	Bar	
16																		
	5.00-16	6	TT	4.00E	3.00D,4J,4 1/2J	5.5	26.8	13	80	A6	84	1100	A8	76	880	410	4	
	5.50-16	6	TT	4.00E	3.5D,4.5E	6.2	28.3	13	84	A6	86	1170	A8	78	935	370	4	
	6.00-16	8	TT	4.50E	4.00E,4.25KA	6.3	29.1	13.1	87.4	A6	94	1477	A8	91	1355	450	5	
	6.00-16	6	TT	4.50E	4.00E,4.25KA	6.3	29.1	13.1	87.4	A6	88	1234	A8	85	1135	360	4	
	6.50-16	6	TT	4.50E	4.00E,4.25KA	6.8	30.0	13.6	90.4	A6	91	1355	A8	88	1234	330	3	
	7.50-16	6	TT	5.50F	6LB	8	31.8	14.4	97.8	A6	98	2095	A8	94	1477	300	3	
	7.50-16	8	TT	5.50F	6LB	8	31.811	14.41	97.75	A6	102	1930	A8	99	1565	390	4	
	10.00-16	10	TL	W8L	8LB	10.8	35.2	16.5	105.6	A6	119	2680	A8	111	2405	340	3	
18																		
	7.50-18	8	TT	5.50F	-	8.2	34.4	16	103	A6	106	2094	A8	102	1873	390	4	
20																		
	6.50-20	6	TT	5.00F	4E,5.5F	7.1	34	16	101	A6	97	1610	A8	93	1433	310	3	
	7.50-20	6	TT	5.50F	5.0F	8.1	36	17	107	A6	103	1930	A8	99	1565	280	3	
	7.50-20	8	TT	5.50F	5.0F	8.1	36	17	107	A6	108	2204	A8	105	2039	385	4	

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 – Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR:

GRI

28, Joseph's Lane, Colombo 4, Sri Lanka

Tel: +94 11 259 8831 Fax: +94 11 255 1091 Email: info@gritires.com

WWW.GRITIRES.COM