



STURDY AND ROBUST NYLON CASING

Provides extraordinary impact and shock resistance
Extensive tire life

CUT & CHIP RESISTANT TREAD COMPOUND

Ensures resistance against wear and cuts
Extensive tire life

UNIQUE TREAD DESIGN

Enables higher traction
Better productivity

LT122 (L2)

BIAS TIRES BUILT FOR LOADERS



- Best suited for loading operations
- Unique inter lug design offers unmatched puncture resistance and durability

TYRE SIZE
24.0
14.9-24

Traction



Tire Life



Ground Stability



Puncture Resistance



TECHNICAL DATA

TYRE SIZE	PR	TT / TL	RIM		Unloaded Inflated Dimension		SLR	RC	At Speed 40 kmph						
					SW	OD			Speed Index	Load Index	Inflation Pressure				
			Rec. inch	Alt. inch	± 2 % mm	± 2 % mm	mm	± 2.5 % mm			MAX. LOAD	Kgs	KPA	BAR	
24.0															
14.9-24	12	TL	DW13	W12	378	1265	570	3800	A8	145.0	2900	290	2.9		

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 – Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR:

GRI

28, Joseph's Lane, Colombo 4, Sri Lanka

Tel: +94 11 259 8831 Fax: +94 11 255 1091 Email: info@gritires.com

WWW.GRITIRES.COM