





LIFT EX PNEUMATIC FORKLIFT TIRE

A Pneumatic Material Handling Tire engineered for heavy duty use on forklift trucks and other industrial vehicles. These tires have a large footprint and a tread that assures optimal traction under every condition. The sidewalls are enhanced by multiple layers of reinforcement and a wide rim guard. The augmented contact area and the reinforced sidewall ensures high load carrying capacity.

LIFT EX is best suited for...

- High abrasion resistance
- Maximum stability, safety and comfort
- Heavy Duty Construction
- Extremely low rolling resistance





TECHNICAL DATA

			Π/ TL	TUBE	VALVE	FLAP	RIM		Unloaded Inflated Dimension			LOAD CAPACITY										
												FORK LIFT TRUCK UP TO 16 MPH / 25 KMPH			OTHER VEHIC			E H (A5)	STATIC LOADER 0 MPH		Inflation	
	TYRE SIZE	PR									Speed Index	MAX. LOAD LOAD WHEEL				MAX. LOAD LOAD WHEEL		MAX. LOAD STEERING WHEEL		MAX. LOAD		Pressure
									sw	OD												
							Rec. inch	Alt. inch	±2% Inch			Load Index	lbs	Load Index	lbs	Load Index	lbs	Load Index	lbs	Load Index	lbs	kPa
8.0	5.00-8	8	TT	5.00-8	JS2	5.00-8	3.0D	3.25	5.5	18.8	A 5	115	2720	106	2095	115	2720	106	2095	120		825
	18x7-8	16	TT	18X7-8	V3-02-05	18X7-8	4.33 R	5.00F	7.1	18.6	A 5	134	4730	125	3635	134	4730	125	3635	140	5490	999.775
9.0																						
	6.00-9	10	TT	6.00-9	JS2	6.00-9	4.00E		6.6	21.26	A 5	127	3855	118	2910	127	3855	118	2910	132	4400	850
10.0																						
	6.50-10	10	TT	6.50-10	JS2	6.50-10	5.00F	5.50F	7.2	23.3	A 5	131	4300	122	3305	131	4300	122	3305	136	4995	775
	23X9-10	20	TT	23X9-10	TR177A	23X9-10	6.5F		9.3	22.8	A5	151	7605	142	5840	151	7605	142	5840	156	8820	1000
12.0	7.00-12	12	TT	7.00-12	TR75A	7.00-12	5.00S		7.7	26.5	A5	142	5840	133	4540	142	5840	133	4540	147	6780	850
	7.00-12	12	TT	7.00-12	TR75A	7.00-12	5.00S		7.7	26.5	A5 A 5	142	6000	135	4540	142	6000	135	4540	147	7055	900
15.0	7.00-12	14		7.00-12	TR75A	7.00-12	5.005		7.7	20.5	AJ	143	0000	134	4075	143	0000	134	4075	140	7033	300
	8.15-15	14	TT	8.15-15	TR75A	8.15-15	7	7.0BD	8.6	27.8	A 5	154	8265	145	6395	154	8265	145	6395	159	9660	900
	8.25-15	14	TT	7.50/8.25-15	TR177A	7.00/8.25-15	6.5	7	9.7	33.1	A 5	158	9360	149	7165	158	9360	149	7165	163	10825	799.82
	250-15	16	TT	250-15	TR 77 A	250/300/10L-15	7.5		9.1	28.9	A 5	159	9600	150	7385	159	9600	150	7385	164	11155	830
	250-15	20	TT	250-15	TR 77 A	250/300/10L-15	7.5		9.1	28.9	A 5	165	11465	156	8820	165	11465	156	8820	170	13320	1050
	300-15	18	TT	300-15	TR 77 A	250/300/10L-15	8		10.9	33.5	A 5	170	13225	161	10195	170	13225	161	10195	175	15210	750
	300-15	20	TT	300-15	TR 77 A	250/300/10L-15	8		10.9	32.09	A 5	172	13980	163	10750	172	13980	163	10750	177	16230	950

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. If any tire covered by this warranty is identified as unserviceable tire due to a material / workmanship /any other manufacturing defect, we will either repair the tire or make an allowance on purchase of new tire as per the current price of a new tire by the percentage of original tread worn off at the time of making the claim.

The cost of transportation, service, and sales tax already paid will be borne by the owner of the claimed tire. This limited warranty is made for the exclusive benefit of the tire owner actually using the product. No other warranty of liability, expressed or implied, is applicable to this limited warranty or to our products.

Business today is complex, ambiguous and uncertain – a little like life itself. To help you advance and attain your goals, you need something that is completely the opposite. GRI tires are robustly engineered and relentlessly tested to give you assured performance, so you can get a grip on things that really matter to you. Whatever your ambition, GRI will get you there.

DISTRIBUTOR: