

PEAKMASTER[®]

PREMIUM



SPECIAL COMPOUND WITH GREATER TREAD VOLUME

For reduced heat build-up in center with low abrasion loss
Extensive tire life

WIDE PROFILE & BOLD TREAD PATTERN

For good traction, superior self cleaning and low rolling resistance
Higher productivity

GREATER LUG DEPTH AND OPTIMIZED ASPECT RATIO

For excellent grip and assured performance
Extensive tire life



PEAKMASTER

SOLID RESILIENT TIRES
BUILT FOR FORKLIFTS



16 Hours /A day in Operation

- Non-marker tire for a clean run on light colored surfaces
- Able to take on tough and rugged terrains with confidence
- Very quiet running and outstanding lateral guidance
- High-tensile creel bead wires ensure ideal wheel fitment

Energy Savings



Performance



Tire Life



Driving Comfort



3 STAGE TIRE

- Tread Compound
- Centre Compound
- Base Compound
- Bead Weave



TECHNICAL DATA

Tire Size	Rim Size	Profile	Clip on	Tire Dimensions (mm)		Other Vehicles Load Capacity (kg)		Max. Forklift Trucks Load Capacity at 25 km/h. (kg)	
				Max Width $\pm 1\%$	OD $\pm 2\%$	6 km/h	10 km/h	Load Wheel	Steer Wheel
4.00-4	2.10-4	Peakmaster		99	304	535	485	535	412
4.00-4	2.50-C-4	Peakmaster		99	304	535	485	535	412
4.00-8	3.00 D-8	Peakmaster	•	106	406	950	860	950	730
5.00-8	3.00 D-8	Peakmaster	•	120	446	1415	1285	1415	1090
15x4 1/2-8 (125/75-8)	3.00 D-8	Peakmaster	•	114	377	1040	945	1040	800
16x6-8 (150/75-8)	4.33 R-8	Peakmaster	•	151	411	1495	1360	1495	1150
18x7-8 (180/70-8)	4.33 R-8	Peakmaster	•	153	453	2145	1945	2145	1650
140/55-9	4.00 E-9	Peakmaster	•	129	375	1170	1060	1170	900
6.00-9	4.00 E-9	Peakmaster	•	137	519	1885	1710	1885	1450
21x8-9 (200/75-9)	6.00 E-9	Peakmaster	•	186	518	2755	2500	2755	2120
6.50-10	5.00 F-10	Peakmaster	•	160	561	2340	2125	2340	1800
200/50-10	6.50 F-10	Peakmaster	•	190	455	2470	2240	2470	1900
23x9-10 (225/75-10)	6.50 F-10	Peakmaster	•	200	580	3445	3125	3445	2650
7.00-12	5.00 S-12	Peakmaster	•	172	650	2920	2645	2920	2240
23x10-12	8.00 G-12	Peakmaster	•	233	578	3770	3420	3770	2900
27x10-12 (250/75-12)	8.00 G-12	Peakmaster	•	237	677	3900	3540	3900	3000
7.00-15	5.50-15	Peakmaster	•	180	722	3545	3215	3545	2725
7.50-16	6.00-16	Peakmaster		207	777	3965	3540	3965	3060
8.00-16	6.00-16	Peakmaster		207	777	3965	3540	3965	3060
250-15 (250/70-15)	7.00-15	Peakmaster	•	222	722	4745	4310	4745	3650
250-15 (250/70-15)	7.50-15	Peakmaster	•	222	722	4745	4310	4745	3650
8.15-15 (28x9-15)	7.00-15	Peakmaster	•	217	691	3900	3540	3900	3000
8.25-15	6.50-15	Peakmaster	•	212	810	4750	4300	4750	3650
300-15 (315/70-15)	8.00-15	Peakmaster	•	250	824	5850	5310	5850	4500
28x12.5-15 (355/45-15)	9.75-15	Peakmaster	•	292	697	5690	5165	5690	4375
355/65-15	9.75-15	Peakmaster	•	300	819	7085	6430	7800	6000

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 - Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR:

GRI

28, Joseph's Lane, Colombo 4, Sri Lanka
Tel: +94 11 259 8831 Fax: +94 11 255 1091 Email: info@gritires.com

WWW.GRITIRES.COM