



### DUAL ANGLE LUG DESIGN

Enhances flat surface traction  
Better fuel economy

### OPTIMUM LAND TO AIR RATIO

Provides excellent self cleaning action  
Better fuel economy

### HIGH TREAD DEPTH

For higher traction and longer use  
Extensive tire life

### SUPERIOR TREAD COMPOUNDS

Provides stonger casing and offers less wear  
Extensive tire life

## RT100(R1) BIAS TIRES BUILT FOR TRACTORS



- Y Designed for soil preparation and spraying applications
- Y Dual angle lug design provides all round capabilities on and off road applications
- Y Strong nylon casing offers better power transmission
- Y High Number of Lugs for high traction and stability

Traction



Soil Protection



TYRE SIZES		
24.0	28.0	32.0
8.3-24	11.2-28	12.4-32
9.5-24	12.4-28	30.5L32
11.2-24	13.6-28	34.0
12.4-24	14.9-28	16.9-34
13.6-24	16.9-28	18.4-34
14.9-24	30.0	38.0
16.9-24	16.9-30	13.6-38
26.0	18.4-30	15.5-38
18.4-26		16.9-38
23.1-26		18.4-38
		20.8-38

# TECHNICAL DATA

TYRE SIZE	PR	TL / TT	RIM		Unloaded Inflated Dimension		SLR	RC
					SW	OD		
			Rec. inch	Alt. inch	± 2 % mm	± 2 % mm	mm	± 2.5 % mm
<b>24.0</b>								
8.3-24	8	TT	W7		211	995	469	2985
9.5-24	8	TT	W 8	W 7	232	1056	494	3117
11.2-24	8	TT	W 10	W 9	284	1105	515	3249
12.4-24	8	TT	W 11	W 9, W 10	315	1160	535	3524
13.6-24	8	TT	W 12	W 11	345	1210	560	3556
14.9-24	8	TT	W 13	W 11, W 12	378	1265	583	3719
16.9-24	8	TT	W 15 L	W 14 L	429	1335	613	3925
<b>26.0</b>								
18.4-26	12	TT	W 16 L	W 15 L	467	1450	662	4278
23.1-26	12	TT	DW 20B	DW 20B	587	1585	711	4615
<b>28.0</b>								
11.2-28	8	TT	W 10	W 9	284	1205	565	3543
12.4-28	8	TT	W 11	W 9, W 10	315	1260	589	3704
13.6-28	8	TT	W 12	W 11	345	1310	614	4031
14.9-28	8	TT	W 13	W 11, W 12	378	1365	634	4013
16.9-28	8	TT	W 15 L	W 14 L	429	1435	655	4310
16.9-28	12	TT	W 15 L	W 14 L	429	1435	655	4310
<b>30.0</b>								
16.9-30	8	TT	W 15 L	W 14 L	429	1485	687	4501
16.9-30	10	TT	W 15 L	W 14 L	429	1485	687	4501
18.4-30	8	TT	W16L	W 15 L	460	1545	707	4741
18.4-30	12	TT	W16L	W 15 L	460	1545	707	4741
18.4-30	14	TT	W16L	W 15 L	460	1545	707	4741
<b>32.0</b>								
12.4-32	8	TT	W 11	W 9 W 10	315	1360	639	3998
30.5L32	12	TL	DW 27 B		770	1865	831	5520
30.5L32	18	TT	DW 27 B		770	1865	831	5520
<b>34.0</b>								
16.9-34	8	TT	W 15 L	W 14 L	429	1585	738	4650
18.4-34	8	TT	W 16 L	W 15 L	467	1650	766	4850
18.4-34	10	TT	W 16 L	W 15 L	467	1650	766	4850
18.4-34	12	TT	W 16 L	W 15 L	467	1650	766	4850
<b>38.0</b>								
13.6-38	8	TT	W 12	W 11	345	1565	738	4601
15.5-38	8	TT	W 14 L		395	1585	746	4660
16.9-38	8	TT	W 15 L	W 14 L	429	1685	788	4954
18.4-38	8	TT	W 16 L	W 15 L	467	1750	816	5145
18.4-38	12	TT	W 16 L	W 15 L	467	1750	816	5145
20.8-38	10	TT	W18L	W16L	530	1835	852	5395

## LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details.

DISTRIBUTOR:

GRI

28, Joseph's Lane, Colombo 4, Sri Lanka

Tel: +94 11 259 8833 Fax: +94 11 255 1091 Email: info@gritim

WWW.GRITIRESCOM