



45° LUG ANGLE

Ensures higher traction on and off road
Higher productivity

INTER LUG MUD BREAKERS

Provides excellent self-cleaning
Better fuel economy

MULTI-LAYER UNIQUE TIE BAR

Increased lug stability
Eliminate lug base cracks

WIDE TREAD WIDTH

Ensures wide footprint and stability
Less soil compaction

65 SERIES (R1-W)

RADIAL TIRES FOR
HEAVY DUTY TRACTORS



- High tire volume with low inflation pressure provides high traction and greater soil protection
- Best for soil tillage and on the road applications
- Excellent driving comfort in the field and on the road
- Strong casing, impact belts and special compound for extensive longer life

Traction



Roadability



Load Carrying Capacity



Soil Protection



TYRE SIZES			
24.0	28.0	30.0	38.0
440/65R24	440/65R28	540/65R30	540/65R38
480/65R24	480/65R28	34.0	600/65R38
540/65R24	540/65R28	600/65R34	650/65R38
	600/65R28		42.0
			650/65R42

TECHNICAL DATA

TYRE SIZE	LOAD/ SPEED INDEX	TYPE	RIM		Unloaded inflated Dimension \pm 2%		SLR	RC \pm 2.5%	SRI	
					S.W.	O.D.				
			Rec.	Alt.	(mm)	(mm)	(mm)	(mm)	(mm)	
24.0										
440/65R24	135 D / 138 A8	TL	W 14 L	W13, W15	441	1182	538	3546	575	
480/65R24	140 D / 143 A8	TL	W 15 L	W14L	479	1234	562	3730	600	
540/65R24	146 D / 149 A8	TL	W 16 L	W18L	530	1312	590	3930	625	
28.0										
440/65R28	138 D / 141 A8	TL	W 14 L	W13	441	1283	590	3878	625	
480/65R28	142 D / 145 A8	TL	W 15 L	W14L	479	1335	610	4058	650	
540/65R28	149 D / 152 A8	TL	W 16 L	W 18 L	530	1413	643	4253	675	
600/65R28	154 D / 157 A8	TL	DW 20 B	W 18 L	611	1491	670	4470	700	
30.0										
540/65R30	150 D / 153 A8	TL	W 16 L	W 18 L	530	1460	670	4403	700	
34.0										
600/65R34	157 D / 160 A8	TL	D W20B	W18L	611	1644	742	4960	775	
38.0										
540/65R38	153 D / 156 A8	TL	W16L	W18L	530	1667	760	5059	800	
600/65R38	159 D / 162 A8	TL	DW 20 B	W 18 L	611	1745	790	5247	825	
650/65R38	163 D / 166 A8	TL	DW 20 B		645	1811	830	5483	875	
42.0										
650/65R42	165 D / 168 A8	TL	DW 20 B		645	1913	864	5740	925	

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 - Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR:

GRI

28, Joseph's Lane, Colombo 4, Sri Lanka
Tel: +94 11 259 8831 Fax: +94 11 255 1091 Email: info@gritires.com

WWW.GRITIRES.COM