

## HIGH TREAD DEPTH

Superior field traction  
Extensive tire life

## STRONG CASING AND IMPACT BELTS

Prevents stubble damage to tire  
Extensive tire life

## INTER LUG MUD BREAKERS

Provides excellent self-cleaning  
Better fuel economy

## OPTIMIZED LUG ANGLE

Higher traction and ride comfort on and off road  
Higher productivity



## 70 SERIES (R1-W)

RADIAL TIRES FOR  
HEAVY DUTY TRACTORS



- Suitable for several heavy-duty applications such as soil preparation and road transport
- Wide contact patch ensures excellent traction on all surfaces
- Provides long wear, smooth riding and excellent self-cleaning
- Flexible sidewall provides higher rider comfort for less fatigue and minimum soil compaction

Traction



Roadability



Load Carrying Capacity



Soil Protection



TYRE SIZES			
24.0	28.0	30.0	38.0
360/70R24	380/70R28	480/70R30	480/70R38
380/70R24	420/70R28	600/70R30	520/70R38
420/70R24	480/70R28	34.0	580/70R38
480/70R24		480/70R34	710/70R38
		520/70R34	42.0
			710/70R42
			620/70R42

## TECHNICAL DATA

TYRE SIZE	LOAD / SPEED INDEX	TYPE	RIM		Unloaded inflated Dimension $\pm$ 2%		SLR	RC $\pm$ 2.5%	SRI	
					S.W.	O.D.				
			Rec.	Alt.	(Inch)	(Inch)				(Inch)
<b>24.0</b>										
360/70R24	122 A8/ B	TL	W 11	W 10, W12	14	45	20	134	22	
380/70R24	125 A8/ B	TL	W 12	W 11, W13	15	47	21	140	23	
420/70R24	130 A8/ B	TL	W 13	W 12 , W14 L	16	49	22	145	24	
480/70R24	138 A8/ B	TL	W 15 L	W 14 L , W 16 L	19	52	23	153	25	
<b>28.0</b>										
380/70R28	127 A8/ B	TL	W 12	W 11 , W13	15	51	23	153	25	
420/70R28	133 A8/ B	TL	W 13	W 12 , W14 L	16	53	24	158	26	
480/70R28	140 A8/ B	TL	W 15 L	W 14 L , W 16 L	19	56	25	165	27	
<b>30.0</b>										
420/70R30	134 A8/ B	TL	W 13	W 12 , W14 L	16	55	25	164	27	
480/70R30	141 A8/ B	TL	W 15 L	W 14 L , W 16 L	19	58	26	170	28	
600/70R30	152 A8/ B	TL	DW 20 B	DW18 L, W18L	23	63	28	188	30	
<b>34.0</b>										
480/70R34	149 A8/ B	TL	W 15 L	W 14 L , W 16 L	19	62	28	187	30	
520/70R34	148 A8/ B	TL	W 16 L	W 15 L, W 18 L	20	65	29	193	31	
<b>38.0</b>										
480/70R38	145 A8/ B	TL	W 15 L	W 14 L , W 16 L	19	66	30	197	31	
520/70R38	150 A8/ B	TL	W 16 L	W 15 L, W 18 L	20	69	31	209	32	
580/70R38	155 A8/ B	TL	W 18 L		23	72	32	217	34	
710/70R38	166 A8/ B	TL	DW 23 B		28	77	34	226	36	
<b>42.0</b>										
710/70R42	173 A8/ B	TL	DW 23 B		28	81	36	243	38	

### LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 - Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR:

### GRI

28, Joseph's Lane, Colombo 4, Sri Lanka  
Tel: +94 11 259 8831 Fax: +94 11 255 1091 Email: info@gritires.com

WWW.GRITIRES.COM