



DUAL ANGLE LUG DESIGN

Enhances flat surface traction
Better fuel economy

OPTIMUM LAND TO SEA RATIO

Provides excellent self cleaning and traction
Better fuel economy

HIGH TREAD DEPTH

For higher traction and longer use
Extensive tire life

SUPERIOR TREAD COMPOUNDS

Provides stronger casing and offers less wear
Extensive tire life

RT100 (R1)

BIAS TIRES BUILT FOR TRACTORS



- Designed for soil preparation and spraying applications
- Dual angle lug design provides all round capabilities in on and off road applications
- Strong nylon casing offers better power transmission
- Higher Number of Lugs for higher traction and stability

Traction



Soil Protection



TYRE SIZES			
24.0	26.0	28.0	32.0
8.3-24 *	18.4-26	11.2-28	12.4-32 *
9.5-24 *	23.1-26 *	12.4-28	34.0
11.2-24		13.6-28	16.9-34
12.4-24		14.9-28	18.4-34
13.6-24		16.9-28	38.0
14.9-24		30.0	13.6-38 *
16.9-24		16.9-30	15.5-38
		18.4-30	16.9-38
			18.4-38
			20.8-38 *

TECHNICAL DATA

TYRE SIZE	PR	TL / TT	RIM		Unloaded Inflated Dimension		SLR	RC	
					SW	OD			
			Rec. inch	Alt. inch	± 2 % Inch	± 2 % Inch	Inch	± 2.5 inch	
24.0									
8.3-24 *	8	TT	W7		8.3	39.2	18	118	
9.5-24 *	8	TT	W 8	W 7	9.1	41.6	19.4	122.7	
11.2-24	8	TT	W 10	W 9	11.2	43.5	20.3	127.9	
12.4-24	8	TT	W 11	W 9, W 10	12.4	45.7	21.1	138.7	
13.6-24	8	TT	W 12	W 11	13.6	47.6	22.0	140.0	
14.9-24	8	TT	W 13	W 11, W 12	14.9	49.8	23.0	146.4	
16.9-24	8	TT	W 15 L	W 14 L	16.9	52.5	24.0	155.0	
26.0									
18.4-26	12	TT	W 16 L	W 15 L	18.4	57.1	26.1	168.4	
23.1-26 *	12	TT	DW 20B	DW 20B	23.1	62.4	28.0	182.0	
28.0									
11.2-28	8	TT	W 10	W 9	11.2	47.4	22.2	139.0	
12.4-28	8	TT	W 11	W 9, W 10	12.8	49.6	23.2	145.8	
13.6-28	8	TT	W 12	W 11	13.6	51.6	24.2	158.7	
14.9-28	8	TT	W 13	W 11, W 12	14.9	53.7	25.0	158.0	
16.9-28	8	TT	W 15 L	W 14 L	16.9	55.9	25.8	169.7	
16.9-28	12	TT	W 15 L	W 14 L	16.9	55.9	25.8	169.7	
30.0									
16.9-30	8	TT	W 15 L	W 14 L	16.9	58.5	27.0	177.2	
16.9-30 *	10	TT	W 15 L	W 14 L	16.9	58.5	27.0	177.2	
18.4-30	8	TT	W16L	W 15 L	18.1	60.8	27.8	186.7	
18.4-30	12	TT	W16L	W 15 L	18.1	60.8	27.8	186.7	
18.4-30	14	TT	W16L	W 15 L	18.1	60.8	27.8	186.7	
32.0									
12.4-32 *	8	TT	W 11	W 9 W 10	12.8	53.5	25.2	157.4	
34.0									
16.9-34	8	TT	W 15 L	W 14 L	16.9	62.4	29.1	183.1	
18.4-34	8	TT	W 16 L	W 15 L	18.4	65.0	30.2	190.9	
18.4-34	10	TT	W 16 L	W 15 L	18.4	65.0	30.2	190.9	
18.4-34	12	TT	W 16 L	W 15 L	18.4	65.0	30.2	190.9	
38.0									
13.6-38 *	8	TT	W 12	W 11	13.6	61.6	29.1	181.1	
15.5-38	8	TT	W 14 L		15.6	62.4	29.4	183.5	
16.9-38	8	TT	W 15 L	W 14 L	16.9	66.3	31.0	195.0	
18.4-38	8	TT	W 16 L	W 15 L	18.4	68.9	32.1	202.6	
18.4-38 *	12	TT	W 16 L	W 15 L	18.4	68.9	32.1	202.6	
20.8-38 *	10	TT	W18L	W16L	20.9	72.2	34	212	

* Under Development

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

DISTRIBUTOR:

GRI

28, Joseph's Lane, Colombo 4, Sri Lanka
Tel: +94 11 259 8831 Fax: +94 11 255 1091 Email: info@gritires.com

WWW.GRITIRES.COM