

INTER LUG MUD BREAKERS

Provides excellent self-cleaning
Better fuel economy

ROUNDED SHOULDERS

Minimize field and crop damage
Less soil compaction

NARROW PROFILE

Higher directional stability
Higher productivity

STRONG NYLON CASING & IMPACT BELTS

Provides high load capacity and durability
Extensive tire life



95 SERIES (R1-W)

RADIAL TIRES FOR
ROW CROP APPLICATIONS



- Special line of radial tires for row crop and spraying applications
- Cut and wear resistant compound increases productivity ensures extensive tire life
- Robust casing and belts provide longer tire life

Traction



Roadability



Load Carrying Capacity



Soil Protection



TYRE SIZES	
32.0	48.0
270/95R32	230/95R48
46.0	270/95R48
300/95R46	340/85R48
380/90R46	

TECHNICAL DATA

TYRE SIZE	LOAD INDEX / SPEED INDEX	TYPE	RIM		Unloaded inflated Dimension ± 2%		SLR	RC ± 2.5%	SRI	SPEED	LOAD CAPACITY (KG / TIRE)												
			Rec.	Alt.	S.W.	O.D.					0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4			
					(mm)	(mm)															(mm)	(mm)	(mm)
32.0																							
270/95R32 (11.2R32)	136 A8 / B	TL	W 9	W 8, W 10	275	1327	614	4044	625	bar / kmph	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4			
											50	875	1145	1390	1525	1615	1770	1930	2085	2240			
											40	875	1145	1390	1525	1615	1770	1930	2085	2240			
											30	935	1225	1485	1630	1730	1895	2065	2230	2395			
											10	1045	1315	1615	1920	2220	2285	2555	2825	3095	3360		
46.0																							
300/95R46 (12.4R46)	148 A8 / B	TL	W 9	W 10, DW 10, W11	295	1738	812	5318	825	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
											50	1105	1295	1485	1670	1860	2015	2205	2365	2585	2805	2995	3150
											40	1105	1295	1485	1670	1860	2015	2205	2365	2585	2805	2995	3150
											30	1180	1385	1590	1790	1990	2160	2360	2530	2765	3005	3205	3375
											20	1355	1590	1825	2055	2285	2480	2710	2905	3175	3450	3680	3875
380/90R46 * (14.9R46)	155 A8 / B	TL	W 12	W 11, W 13	380	1852	859	5596	875	bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6					
											50	1785	2285	2790	3065	3295	3605	3875					
											40	1785	2285	2790	3065	3295	3605	3875					
											30	1910	2450	2990	3285	3530	3860	4150					
											10	2095	2740	3315	3955	4540	4715	5235	5815				
48.0																							
230/95R48 (9.5R48)	136 A8 / B	TL	W 8	W 7	238	1656	792	5085	800	bar / kmph	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4			
											50	1095	1430	1735	1905	2020	2210	2410	2605	2800			
270/95R48 (11.2R48)	144 A8 / B	TL	W 9	W 8, W 10	275	1733	820	5351	825	bar / kmph	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4			
											50	1095	1430	1735	1905	2020	2210	2410	2605	2800			
											40	1095	1430	1735	1905	2020	2210	2410	2605	2800			
											30	1170	1530	1860	2040	2160	2365	2580	2785	2995			
340/85R48 (13.6R48)	152 A8 / B	TL	W 12	W 11	353	1797	855	5572	875	bar / kmph	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4			
											50	1390	1815	2200	2420	2560	2805	3055	3300	3550			
											40	1390	1815	2200	2420	2560	2805	3055	3300	3550			
											30	1485	1940	2355	2585	2740	3000	3270	3535	3800			
											10	1655	2085	2560	3045	3520	3625	4050	4475	4905	5325		

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 - Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR:

GRI

28, Joseph's Lane, Colombo 4, Sri Lanka
Tel: +94 11 259 8831 Fax: +94 11 255 1091 Email: info@gritires.com

WWW.GRITIRES.COM