



INTER LUG MUD BREAKERS

Provides excellent self-cleaning
Better fuel economy

ROUNDED SHOULDERS

Minimize field and crop damage
Less soil compaction

NARROW PROFILE

Higher directional stability
Higher productivity

STRONG NYLON CASING & IMPACT BELTS

Provides high load capacity and durability
Extensive tire life

95 SERIES (R1W)

RADIAL TIRES FOR
ROW CROP APPLICATIONS



- Special line of radial tires for row crop and spraying applications
- Cut and wear resistant compound increases productivity ensures extensive tire life
- Robust casing and belts provide longer tire life

Traction



Roadability



Load Carrying Capacity



Soil Protection



TYRE SIZES	
32.0	48.0
270/95R32	230/95R48
46.0	270/95R48
300/95R46	340/85R48
380/90R46	

TECHNICAL DATA

TYRE SIZE	LOAD INDEX / SPEED INDEX	TYPE	RIM		Unloaded inflated Dimension ± 2%		SLR	RC ± 2.5%	SRI	SPEED	LOAD CAPACITY (LBS / TIRE)													
			Rec.	Alt.	S.W. (Inch)	O.D. (Inch)					(Inch)	(Inch)	(Inch)	(Inch)	(Inch)	(Inch)	(Inch)	(Inch)						
32.0																								
270/95R32 (11.2R32)	136 A8 / B	TL	W 9	W 8, W 10	10.83	52.2	24	159	24.6		psi / mph	12	17	23	29	35	40	46	52	58	65			
											30	1930	2525	3060	3365	3560	3900	4260	4595	4940				
											25	1930	2525	3060	3365	3560	3900	4260	4595	4940				
											20	2065	2700	3275	3600	3814	4175	4550	4915	5290				
											5	2305	2900	3560	4235	4895	5040	5635	6225	6825	7410			
46.0																								
300/95R46 (12.4R46)	148 A8 / B	TL	W 9	W 10, DW 10, W 11	12	68.4	32	209	32.5		psi / mph	9	12	14	17	20	23	29	35	40	46	52	58	65
											30	2430	2855	3270	3680	4095	4445	4860	5210	5695	6184	6595	6945	
											25	2430	2855	3270	3680	4095	4445	4860	5210	5695	6184	6595	6945	
											20	2605	3055	3505	3940	4390	4760	5205	5580	6100	6625	7065	7440	
											15	2987	3510	4025	4525	5040	5465	5980	6405	7005	7606	8115	8540	
5	3355	3940	4515	5085	5660	6140	6715	7195	7865	8532	9110	9590	10415											
380/90R46 * (14.9R46)	155 A8 / B	TL	W 12	W 11, W 13	15	72.9	34	220	34.4		psi	12	17	23	29	35	40	46	52					
											30	3935	5050	6150	6760	7260	7950	8545						
											25	3535	5050	6150	6760	7260	7950	8545						
											20	4210	5400	6590	7235	7780	8510	9150						
											5	4620	6035	7310	8715	10010	10390	11540	12820					
48.0																								
230/95R48 (9.5R48)	136 A8 / B	TL	W 8	W 7	9	65.2	31	200	31.5		psi / mph	12	17	23	29	35	40	46	52	58	65			
											30	1930	2525	3060	3365	3560	3900	4250	4595	4940				
											25	1930	2525	3060	3365	3560	3900	4250	4595	4940				
											20	2065	2700	3275	3600	3810	4175	4550	4915	5285				
											5	2305	2900	3560	4235	4895	5040	5635	6225	6820	7410			
270/95R48 (11.2R48)	144 A8 / B	TL	W 9	W 8, W 10	11	68.2	32	211	32.5		psi / mph	12	17	23	29	35	40	46	52	58	65			
											30	2415	3155	3825	4200	4455	4870	5315	5745	6175				
											25	2415	3155	3825	4200	4455	4870	5315	5745	6175				
											20	2580	3375	4100	4495	4760	5215	5690	6140	6605				
											5	2875	3625	4455	5290	6120	6305	7045	7780	8520	9260			
340/85R48 (13.6R48)	152 A8 / B	TL	W 12	W 11	14	70.7	34	219	34.4		psi / mph	12	17	23	29	35	40	46	52	58	65			
											30	3060	4000	4850	5330	5645	6185	6740	7280	7825				
											25	3060	4000	4850	5330	5645	6185	6740	7280	7825				
											20	3275	4280	5190	5705	6040	6615	7210	7790	8375				
											5	3655	4595	5640	6710	7760	7985	8930	9870	10810	11740			

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 - Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR:

GRI

28, Joseph's Lane, Colombo 4, Sri Lanka
Tel: +94 11 259 8831 Fax: +94 11 255 1091 Email: info@gritires.com