



SHOULDER BLOCK DESIGN

Provides higher resistance to side impacts Extensive tire life

TRIPLE CIRCUMFERENTIAL RIBS

High load capacity and excellent self cleaning Better fuel economy

RAISED CENTER RIBS WITH OPTIMUM ANGLE CRISSCROSS GROOVES

Provides better roadability Higher productivity

WEAR RESISTANT COMPOUND

Higher productivity Extensive tire life

RIB3 (F3) BIAS TIRES BUILT FOR IMPLEMENT APPLICATIONS



- Designed for implements and trailers in soil tillage applications
- Offers high load carrying capacity and minimum soil compaction
- Shoulder block design promotes excellent field traction

Traction



| TYRE SIZES | | | | | | | |
|----------------|-----------------------------|--|--|--|--|--|--|
| 15.3 | 17.0 | | | | | | |
| 10.0/75-15.3 | 15.0/55-17 * | | | | | | |
| 11.5/80-15.3 * | 19.0/45-17 * 18.0 | | | | | | |
| 12.5/80-15.3 * | | | | | | | |
| | 12.5/80-18 | | | | | | |

TECHNICAL DATA

| | TYRE SIZE | PR | TT / | RIM | | Unloaded Inflated Dimension | | SLR | RC | | |
|------|----------------|----|---------------------|--------------|--------------|-----------------------------------|-------------|------|-----------------|--|--|
| | | | TL | | | sw | OD | | | | |
| | | | | Rec. inch | Alt. inch | ±2% Inch | ±2% Inch | Inch | ± 2.5 % inch | | |
| 15.3 | | | | | | | | | | | |
| | 10.0/75-15.3 | 10 | TL | 9.0 | | 10.8 | 29.9 | 14 | 88 | | |
| | 10.0/75-15.3 | 14 | TL | 9.0 | | 10.8 | 29.9 | 14 | 88 | | |
| | 11.5/80-15.3 * | 10 | TL | 9.0 | | 11.7 | 33.3 | 14 | 97 | | |
| | 11.5/80-15.3 * | 12 | TL | 9.0 | | 11.7 | 33.3 | 14 | 97 | | |
| | 11.5/80-15.3 * | 14 | TL | 9.0 | | 11.7 | 33.3 | 14 | 97 | | |
| | 11.5/80-15.3 * | 18 | TL | 9.0 | | 11.7 | 33.3 | 14 | 97 | | |
| | 12.5/80-15.3 * | 14 | TL | 9.0 | | 12.3 | 35.0 | 15 | 102 | | |
| | 12.5/80-15.3 * | 16 | TL | 9.0 | | 12.3 | 35.0 | 15 | 102 | | |
| 17.0 | | | | | | | | | | | |
| | 15.0/55-17 * | 10 | * Under Development | | | | | | | | |
| | 19.0/45-17 * | 14 | * Under Development | | | | | | | | |
| 18.0 | | | | | | | | | | | |
| | 12.5/80-18 | 12 | TL | W9 | 11.0 | 12.1 | 38.0 | 17 | 111 | | |
| | 12.5/80-18 | 16 | TL | W9 | 11.0 | 12.1 | 38.0 | 17 | 111 | | |

* Under Development

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. Please refer our standard warranty policy for further details

GRI is a leading producer of Specialty Tires from Sri Lanka with offices in six countries and sales in over 50 countries around the world. GRI produces high-performance Agriculture, Construction and Material Handling Tires. GRI's state-of-the-art factory is the largest in Sri Lanka to produce specialty tires and the first to produce radial agriculture tires. Technological innovation, engineering strength and operational excellence have powered GRI through rapid growth to become a leader in specialty tires. GRI is certified in ISO 9001:2015 - Quality Management, ISO 50001: 2011 – Energy Management and ISO 14001:2004 Environmental Management.

DISTRIBUTOR: